



3/4" Rigging Spring Block

30kN WLL | Hot forged aluminum | Working lines up to 3/4" diameter

FEATURES & BENEFITS

- Medium sized arborist block accepts working lines up to 3/4" (19mm) diameter
- 30 kN WLL / 150 kN MBS
- Hot forged aluminum side plates with rope friendly rounded cheeks
- Precision CNC machined aluminum sheaves with wide bend radii
- Low profile, secure, easy-to-open two stage captive spring pin lock
- High wall, full diameter, improved anchor sling protection
- Wide, concave upper sheave accepts 1 1/8" anchor slings
- Flared sideplates reduce twisting in complex rigging scenarios



ITEM #	56130
MSRP	\$229.99
WORKING LOAD LIMIT (WLL)	30 kN (6,744 lbs.)
MBS	150 kN (33,720 lbs.)
MAX WORKING LINE DIAMETER	3/4 in (19mm)
MAX SLING DIAMETER	1 1/8 in (29mm)
UPPER SHEAVE DIAMETER	1.95 in (50mm)
LOWER SHEAVE DIAMETER	2.9 in (74mm)
HEIGHT	7 in (191mm)
WIDTH	4 in (102mm)
WEIGHT	3.6 lbs. (1.6 kg)
SIDEPLATE MATERIAL	Aluminum
SHEAVE MATERIAL	Aluminum
AXLE MATERIAL	Stainless Steel
UPC	723466953009
HTS	8483.50.9040
COUNTRY OF ORIGIN	Taiwan



41630	Rigging Block with 3/4" 2-8' Loopie	\$259.99
41631	Rigging Block with 5/8" 2-6' Loopie	\$253.99
41633	Rigging Block with 3/4" Ultra Sling	\$294.99
41632	Rigging Block with 5/8" Ultra Sling	\$285.99

01282021NSB