

**DMM ANCHOR RINGS**

# **SIMPLE AND PERFECTLY FORMED**



**DMM**  
**PROFESSIONAL**

**FOR MORE INFORMATION CONTACT DMM:**

**LLANBERIS, GWYNEDD, WALES  
UNITED KINGDOM LL55 4EL**

TEL: +44 [0]1286 873 502

FAX: +44 [0]1286 872 090

EMAIL: [PROFESSIONAL@DMMWALES.COM](mailto:PROFESSIONAL@DMMWALES.COM)

[WWW.DMMWALES.COM](http://WWW.DMMWALES.COM)



## DMM ANCHOR RINGS

Certified anchor elements – simple and functional!  
DMM Anchor Rings are junctions which can accommodate a number of textile elements, or up to four carabiners. A 'must have' bit of kit for anyone who works at height.

### GENERIC FEATURES

- Helps organise single or multiple attachments
- Compatible with a wide range of hardware and textile connecting components
- Four sizes – 26, 28, 34, 40 mm internal diameter
- 12 mm circular cross section is the optimum contact dimension for many carabiners
- Combines beautifully with DMM Revolver Locksafe carabiner to create a 'swinging captive eye'
- Certified static and dynamic strengths
- Solid construction provides for good abrasion resistance
- Individual serial marking
- Made in Wales, UK

### SUGGESTED AREAS OF APPLICATION

- Fall Protection
- Temporary Horizontal Lifelines
- Complex lightweight rigging
- Rescue
- Universal connection point
- Stretcher suspension systems
- Tree care

### TECHNICAL SPECIFICATIONS

- CE Certified to EN795B:1997  
[Transportable temporary anchor devices]
- CNC machined from 7075 T6 aluminium for high strength to weight ratio
- Anodised to EN12373-1:2001 Class 10E1 for corrosion protection

### PERFORMANCE

- R500-26, 28, 34, 40  
Minimum breaking strength [MBS]: 30 kN  
Working Load Limit [WLL]: 6 kN

Guidance specific to tree climbing applications can be found in at [www.treemagineers.com](http://www.treemagineers.com)

# DMM PROFESSIONAL